

# 84022 LED CG-S

Safety and Exit Sign Luminaires with High Ingress Protection




## 84022 LED CG-S

- Round safety luminaire with LED technology with high protection class (IP65) for indoor and outdoor use
- Robust construction from aluminium diecast with powder coating (UV stabilised)
- High impact resistant (IK08) diffuser made of UV stabilised polycarbonate
- Two waterproof cable infeeds (IP65) and double terminal for through-wiring
- Spacing up to 17 m from luminaire to luminaire for escape route and wide area illumination
- Minimum service requirement due to high service life of the LEDs (50,000 hours)
- Shortened inspection effort due to CEWA GUARD technology
- Automatic function monitoring of up to 20 luminaires per circuit
- Reduced installation expenditure with STAR technology
- Freely programmable mixed operation of the switching modes per luminaire in one circuit

84022 LED CG-S




Dimensions in mm



Luminous flux $\Phi_N$	600 lm
Luminous flux $\Phi_E/\Phi_N$ at the end of rated operating time	100 %
Housing material	Aluminium diecast, PC
Housing colour	White sim. RAL 9010
Weight	1.85 kg
Type of mounting	Wall and ceiling mounting
Terminals	2 x 3 x 2.5 mm <sup>2</sup>
Connection voltage	220 – 240 V AC, 50/60 Hz 176 – 275 V DC
Power consumption mains operation (apparent power/effective power)	16.9 VA / 9.6 W
Current consumption- battery operating (220 V)	47 mA
Inrush current	3 A
Permissible temperature range	-20 °C to +40 °C
Light source	LowPower LEDs 42 x 180 mW, 4000 K

### Ordering details

Type	Scope of supply	Order No
84022 LED CG-S	Round safety luminaire, including LED Supply and CG-S technology (20 addresses)	40071351531



Light distribution curve 84022 LED CG-S

### Engineering help for 84022 LED CG-S for E = 1.0 Lx (0.5 lx)

Measuring level 0.02 m, maintenance factor MF = 80 %, battery operation, distances in m

Mounting height [m]	Types of mounting	Mounting diagrams			
		L1	L2	L3	L4
2.5	Ceiling mounting	4.9 (6.0)	11.9 (14.5)	4.9 (6.0)	11.9 (14.5)
3.0	Escape route centre	5.2 (6.5)	12.9 (15.7)	5.2 (6.5)	12.9 (15.7)
3.5		5.5 (6.9)	13.8 (16.8)	5.5 (6.9)	13.8 (16.8)
4.0		5.7 (7.2)	14.5 (17.8)	5.7 (7.2)	14.5 (17.8)
4.5		5.9 (7.6)	15.1 (18.7)	5.9 (7.6)	15.1 (18.7)
5.0		6.1 (7.8)	15.6 (19.5)	6.1 (7.8)	15.6 (19.5)
5.5		6.2 (8.1)	16.1 (20.3)	6.2 (8.1)	16.1 (20.3)
6.0		6.2 (8.3)	16.5 (20.9)	6.2 (8.3)	16.5 (20.9)
6.5		6.2 (8.4)	16.8 (21.5)	6.2 (8.4)	16.8 (21.5)
7.0		6.2 (8.6)	17.1 (22.1)	6.2 (8.6)	17.1 (22.1)
7.5		6.2 (8.7)	17.3 (22.5)	6.2 (8.7)	17.3 (22.5)
8.0		6.1 (8.7)	17.5 (23.0)	6.1 (8.7)	17.5 (23.0)
8.5		5.9 (8.8)	17.6 (23.4)	5.9 (8.8)	17.6 (23.4)
9.0		5.7 (8.8)	17.6 (23.7)	5.7 (8.8)	17.6 (23.7)
9.5		5.5 (8.8)	17.6 (24.0)	5.5 (8.8)	17.6 (24.0)
10.0		5.2 (8.8)	17.5 (24.2)	5.2 (8.8)	17.5 (24.2)
2.2	Wall mounting	3.3 (6.0)	8.5 (14.5)	3.3 (6.0)	8.5 (14.5)
2.5		3.3 (6.9)	8.5 (16.8)	3.3 (6.9)	8.5 (16.8)
3.0		3.1 (7.6)	8.4 (18.7)	3.1 (7.6)	8.4 (18.7)
3.5		2.8 (8.3)	8.1 (20.9)	2.8 (8.3)	8.1 (20.9)
4.0		2.4 (8.6)	7.7 (22.1)	2.4 (8.6)	7.7 (22.1)
2.5	Ceiling mounting	3.7 (4.4)	10.2 (12.3)	3.7 (4.4)	10.2 (12.2)
3.0	Room illumination	3.9 (4.8)	11.1 (13.4)	3.9 (4.7)	11.1 (13.3)
3.5		4.1 (5.0)	11.9 (14.4)	4.1 (5.0)	11.8 (14.3)
4.0		4.2 (5.2)	12.6 (15.3)	4.2 (5.2)	12.6 (15.3)
4.5		4.3 (5.4)	13.2 (16.1)	4.3 (5.4)	13.2 (16.1)
5.0		4.4 (5.6)	13.8 (16.9)	4.4 (5.6)	13.8 (16.9)
5.5		4.4 (5.7)	14.3 (17.6)	4.4 (5.7)	14.3 (17.6)
6.0		4.5 (5.9)	14.8 (18.3)	4.4 (5.8)	14.7 (18.2)
6.5		4.4 (6.0)	15.2 (18.9)	4.4 (5.9)	15.2 (18.8)
7.0		4.5 (6.0)	15.6 (19.5)	4.4 (6.0)	15.5 (19.4)
7.5		4.4 (6.1)	15.9 (20.0)	4.4 (6.0)	15.9 (19.9)
8.0		4.3 (6.2)	16.2 (20.5)	4.3 (6.1)	16.2 (20.4)
8.5		4.2 (6.1)	16.5 (20.9)	4.2 (6.1)	16.5 (20.9)
9.0		4.1 (6.1)	16.7 (21.4)	4.1 (6.1)	16.7 (21.3)
9.5		4.0 (6.1)	16.9 (21.8)	4.0 (6.0)	16.9 (21.7)
10.0		3.8 (6.1)	17.1 (22.1)	3.8 (6.1)	17.1 (22.1)