


Exit Cube 33042 LED CG-S



Dimensions in mm



Replacement escape sign cube




Exit Cube 33042 LED CG-S


- Exit sign cube with LED Technology for large, wide areas, e.g. warehouses or retail areas
- Robust design with impact-resistance of IK07
- Low operating costs via low connected load
- Minimum maintenance effort via use of LEDs with high service life (50,000 hours)
- Modular design of the polycarbonate cube enables simple and safe mounting by just sliding cube onto installed luminaire
- Easy and flexible mounting options with space to ceiling or chain.
- Optimal perceptibility due to high luminance of the white contrasting colour ($> 500 \text{ cd/m}^2$) acc. DIN 4844-1 / ISO 3864-1 (for bright environments) and high uniformity $L_{\text{min}}/L_{\text{max}} > 0,4$ (in mains operation)
- Reduced operating costs on account of especially low power consumption
- Shorten inspection effort due to CEWA GUARD technology
- Automatic function monitoring for up to 20 luminaires per circuit
- Reduced installation cost with STAR Technology
- Freely programmable mixed operation, allowing the switching of luminaire modes within one circuit

Viewing Distance	40 m
Luminous flux Φ_E/Φ_N at the end of rated operating time	100 %
Housing material	Cube: PMMA; enclosure: coated steel sheet
Housing colour	White RAL 9010
Weight	Luminaire 1.6 kg Cube: 3,1 kg
Type of mounting	Ceiling mounting
Connection terminals	Loop terminals 2.5 mm ²
Connection voltage	220 - 240 V AC, 50/60 Hz 176 - 275 V DC
Current consumption with battery operation	46 mA
Power consumption mains operation (apparent power / effective power)	17.6 VA / 10.6 W
Permissible temperature range	-20 °C bis +40 °C
Light source	HighPower LEDs 8 x 1 W

Ordering details

Scope of supply	Bestell-Nr.
Exit Cube 33042 LED CG-S: Enclosure and exit sign cube, for 40 m viewing distance with LED Supply and CG-S Technology (20 addresses), silkscreened pictograms (arrow left, right, down) acc. to ISO 7010 	40071353422

Ordering details accessories

Scope of supply	Bestell-Nr.
Replacement escape sign cube (40 m viewing distance) silkscreened pictograms (arrow left, right, down) acc. to ISO 7010 	40071354451